



HELUKABEL®

New Product!



Cable Accessories

Cu Earthing Strap

for EMC Applications

CUEARTHINGSTRAP

Cu Earthing Strap



Cu earthing strap

- for EMC applications (interference elimination)
- rounded contacts

Areas of application

- automobile industry
- robots
- control panel construction

Material


- tinned copper

Technical data

- temperature range: -20°C to +125°C
- individual strand size: 0.2 mm
- contact areas made of seamless, pressed ferrules

Note

- other lengths and inner diameters available on request



Contact HELUKABEL GmbH: zubehoer@helukabel.de

Company	Address	E-mail
Name	Postcode, City	<input type="checkbox"/> Yes, I wish to receive the HELUKABEL® e-mail newsletter. (please tick box)
Customer no.	Tel. / Fax	Date

Art. no.	Description	Cross-section mm ²	Length L in mm	Inner diameter B1 in mm	Inner diameter B2 in mm	Amount
11008412	HELU-MB-Cuv-6-150-0406-R	6	150	4,5	6,5	
11008411	HELU-MB-Cuv-6-500-0606-R	6	500	6,5	6,5	
11008421	HELU-MB-CUv-10-200-0606-R	10	200	6,5	6,5	
11008422	HELU-MB-CUv-10-200-0808-R	10	200	8,5	8,5	
11008423	HELU-MB-CUv-10-300-0606-R	10	300	6,5	6,5	
11008424	HELU-MB-CUv-10-300-0808-R	10	300	8,5	8,5	
11008425	HELU-MB-CUv-10-400-0808-R	10	400	8,5	8,5	
11008442	HELU-MB-CUv-16-100-0808-R	16	100	8,5	8,5	
11008378	HELU-MB-CUv-16-200-0808-R	16	200	8,5	8,5	
11008379	HELU-MB-CUv-16-300-0808-R	16	300	8,5	8,5	
11008441	HELU-MB-CUv-16-400-0808-R	16	400	8,5	8,5	
11008461	HELU-MB-CUv-25-200-0808-R	25	200	8,5	8,5	
11008462	HELU-MB-CUv-25-300-0808-R	25	300	8,5	8,5	