

# JZ-HF-CY high flexible, screened control cable for drag chains, oil resistant, EMC-preferred type, meter marking



Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
15961	2 x 1	8,1	50,0	115,0	17
15962	3 G 1	8,4	60,0	142,0	17
15963	4 G 1	9,0	73,0	196,0	17
15964	5 G 1	9,8	81,0	271,0	17
15965	7 G 1	11,2	114,0	307,0	17
15966	12 G 1	13,4	186,0	474,0	17
15967	18 G 1	15,7	254,0	622,0	17
15968	25 G 1	19,0	365,0	828,0	17
15969	34 G 1	21,0	500,0	1049,0	17
15970	41 G 1	22,7	576,0	1257,0	17
15971	50 G 1	24,5	681,0	1437,0	17
15972	65 G 1	27,7	932,0	1823,0	17
15976	2 x 1,5	8,6	64,0	170,0	16
15977	3 G 1,5	9,0	84,0	203,0	16
15978	4 G 1,5	9,8	99,0	243,0	16
15979	5 G 1,5	10,5	120,0	288,0	16
15980	7 G 1,5	12,5	148,0	403,0	16
15981	12 G 1,5	14,8	274,0	592,0	16
15982	18 G 1,5	17,3	386,0	844,0	16
15983	25 G 1,5	21,0	584,0	1155,0	16
15152	41 G 1,5	24,8	867,0	1227,0	16
15153	50 G 1,5	27,3	970,0	1445,0	16
15154	61 G 1,5	29,8	1028,0	1724,0	16

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
15925	3 G 2,5	10,8	140,0	215,0	14
15926	4 G 2,5	11,5	159,0	264,0	14
15927	5 G 2,5	12,9	194,0	344,0	14
15928	7 G 2,5	15,1	234,0	410,0	14
15929	12 G 2,5	18,4	390,0	721,0	14
15155	3 G 4	13,0	178,0	292,0	12
15156	4 G 4	14,2	222,0	372,0	12
15157	5 G 4	15,6	328,0	448,0	12
15158	4 G 6	16,0	305,0	526,0	10
15159	5 G 6	17,5	441,0	632,0	10
15160	4 G 10	21,2	485,0	838,0	8
15161	5 G 10	23,2	610,0	998,0	8
15162	4 G 16	24,1	840,0	1225,0	6
15163	5 G 16	27,0	1050,0	1560,0	6

Dimensions and specifications may be changed without prior notice. (RC01)

## Terminations and straight-through joints

Telephone cables  
Low voltage  
Medium voltage  
Accessories



You can find terminations and straight-through joints in our catalogue Cable Accessories. Request it now at [www.helukabel.de](http://www.helukabel.de)